

SAFETY DATA SHEET

Classified in accordance with 29 CFR 1910.1200

1. Identification

Product identifier: Crude Propylene**Other means of identification****Common name(s),** Joffre C3 Intermediate Product**synonym(s):****SDS number:** NOVA-0013**Recommended use and restriction on use****Recommended use:** Raw material for manufacture of chemicals and polymers.**Restrictions on use:** All uses other than the identified.**Manufacturer/Importer/Supplier/Distributor Information****Manufacturer**

Company Name: NOVA Chemicals
Address: P.O. Box 2518, Station M
Calgary, Alberta, Canada T2P 5C6
Telephone: Product Information: 1-412-490-4063
SDS Information Email: msdsemail@novachem.com

Emergency telephone number:

1-800-561-6682, 1-403-314-8767 (NOVA Chemicals) (24 hours)

1-800-424-9300 (CHEMTREC-USA) (24 hours)

2. Hazard(s) identification

Hazard Classification**Physical Hazards**

Flammable gas	Category 1
Gases under pressure	Liquefied gas

Health Hazards

Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

OSHA hazard(s)

Simple asphyxiant

Label Elements**Hazard Symbol:****Signal Word:** Danger**Hazard Statement:** Extremely flammable gas.
Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.
May cause genetic defects.
May cause cancer.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources. IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up. Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: Contact with liquefied gas may cause irritation and/or frostbite.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
1-Propene	Propylene	115-07-1	65 - 89%
Propane	Dimethylmethane	74-98-6	9 - 32%
1-Propyne	Methyl acetylene	74-99-7	1.1 - 3.7%
1,2-Propadiene	Propadiene	463-49-0	0.6 - 2.2%
1,3-Butadiene	Vinylethylene	106-99-0	0.1 - 1%
Ethane	Methylmethane	74-84-0	0.1 - 0.4%

* All concentrations are percent by weight.

Additional Information: This product may contain very low levels of Naturally Occurring Radioactive Materials (NORM), which have been identified as Radon 222 (CAS No. 14859-67-7) and its main radioactive decay products, Lead 210 (CAS No. 14255-04-0) and Polonium 210 (CAS No. 13981-52-7). See Section 16 - Further information. This product is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

4. First-aid measures

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Seek medical attention.

Ingestion: Ingestion of this product is not a likely route of exposure. Do NOT induce vomiting. Seek medical attention.

Skin Contact: Contact with liquefied gas may cause irritation and/or frostbite. Seek medical attention immediately in the event of frostbite. IF ON SKIN: Wash with plenty of soap and water. Thaw frosted parts with lukewarm water. Do not rub affected area. Remove non-adhering contaminated clothing. Do not

remove adherent material or clothing. Seek medical attention.

Eye contact: Contact with liquefied gas may cause irritation and/or frostbite. Seek medical attention immediately in the event of frostbite. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Frostbite, headache, dizziness, nausea, heartbeat irregularities.

Indication of immediate medical attention and special treatment needed

Treatment: For more detailed medical emergency support information, call 1-800-561-6682 or 1-403-314-8767 (24 hours, NOVA Chemicals Emergency Response). Treat unconsciousness, frostbite, nausea, hypotension, seizures and cardiac arrhythmias in the conventional manner. Sympathomimetics or catecholamines should be avoided or used with caution (lowest effective dose) because of possible cardiac sensitization. Administer oxygen by mask if there is respiratory distress.

5. Fire-fighting measures

General Fire Hazards: Extremely flammable liquefied gas. Vapors may travel considerable distance to a source of ignition and flash back. DO NOT ATTEMPT TO EXTINGUISH A GAS FIRE UNLESS LEAK SOURCE CAN BE ISOLATED AND SHUT OFF. Be aware of possibility of reignition. Vapors may form explosive mixture with air. Consider need for immediate emergency isolation and evacuation. If a pipeline or a storage vessel is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions. Keep containers away from source of heat or fire. Contains gas under pressure; may explode if heated.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use dry chemical, foam, carbon dioxide (CO₂), water spray or fog to extinguish. Use water to cool fire-exposed containers and to protect personnel.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Upon combustion, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Keep upwind. Keep unauthorized personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Immediately withdraw in case of fire and container venting or heat discoloration of a container. Let uncontrolled fires burn off. Avoid inhaling any smoke and combustion materials. Remove and isolate contaminated clothing and shoes. Cool containers with flooding quantities of water until well after the fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Reference Emergency Response Guidebook No. 115 for additional details and instructions.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Isolate area. Keep unauthorized personnel away. Alert stand-by emergency and fire fighting personnel. Monitor surrounding area for buildup of flammable concentrations in air.

Methods and material for containment and cleaning up:

Wear appropriate personal protective equipment. Do not touch or walk through spilled material. In case of leakage, eliminate all ignition sources. Keep upwind. Keep out of low areas. Stop leak if safe to do so. All equipment used when handling the product must be grounded. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Keep area isolated until any detectable flammable gas has been fully dispersed.

Small Spills: Isolate spill or leak area for 50 to 100 meters (164 to 330 feet).

Large Spills: Consider initial downwind evacuation for at least 800 meters (1/2 mile). Evacuate personnel to upwind of the spill area, and position at a safe distance. Use water spray to reduce gas or divert gas cloud drift.

7. Handling and storage**Precautions for safe handling:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity". Take special precautions when cold cutting or breaking into lines, or when cleaning and disposing of empty containers. Radioactive decay products may accumulate over time in scale or deposits in processing equipment (e.g. pumps, filters, piping, etc.). Equipment and piping should be checked for possible treatment (decontamination) prior to maintenance or disposal/salvage. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Conditions for safe storage, including any incompatibilities:

Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Only allow access to authorized persons. Store and handle in properly designed pressure vessels and equipment. Store and use away from heat, sparks, open flame, or any other ignition source. Have appropriate extinguishing capability in storage area (e.g. sprinkler system, portable fire extinguishers) and flammable gas detectors. Storage pressure vessels should be above ground and diked. Store away from incompatible materials. Store according to applicable regulations and standards for flammable materials.

8. Exposure controls/personal protection**Control Parameters****Occupational Exposure Limits**

In the ACGIH TLVs® and BEIs® book, propane (CAS# 74-98-6), 1-Propyne (methylacetylene) (CAS# 74-99-7) and ethane (CAS# 74-84-0) have been identified as being an "Explosion hazard". Propane (CAS# 74-98-6) and ethane (CAS# 74-84-0) have also been identified as a "Simple asphyxiant". Please refer to the ACGIH TLVs® and BEIs® book, latest edition, for additional information.

Chemical Identity	Type	Exposure Limit Values	Source
1-Propene	TWA	500 ppm	US. ACGIH Threshold Limit Values, as amended
Propane	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
1-Propyne	IDLH	2,100 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
	PEL	1,000 ppm 1,650 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	1,000 ppm 1,650 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	1,000 ppm 1,650 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
1,3-Butadiene	TWA	1,000 ppm	US. ACGIH Threshold Limit Values, as amended
	IDLH	1,700 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
	TWA	2 ppm	US. ACGIH Threshold Limit Values, as amended
	OSHA_AC T	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
1,3-Butadiene	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	TWA	1,000 ppm 2,200 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	IDLH	2,000 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
1,3-Butadiene (1,2-Dihydroxy-4-(N-acetylcysteinyl)-butane: Sampling time: End of shift.)	2.5 mg/l (Urine)	ACGIH BEI
1,3-Butadiene (Mixture of N-1- and N-2-(hydroxybutenyl)valine hemoglobin (Hb) adducts: Sampling time: Not critical.)	2.5 pmol/g (Blood)	ACGIH BEI

Appropriate Engineering Controls

Engineering methods to reduce hazardous exposure are preferred controls. Methods include mechanical ventilation (dilution and local exhaust) process or personal enclosure, remote and automated operation, control of process conditions, leak detection and repair systems, and other process modifications. Ensure all exhaust ventilation systems are discharged to outdoors, away from air intakes and ignition sources. Supply sufficient replacement air to make up for air removed by exhaust systems. Administrative (procedure) controls and use of personal protective equipment may also be required.

Individual protection measures, such as personal protective equipment

General information:

Personal protective equipment (PPE) should not be considered a long-term solution to exposure control. Employer programs to properly select, fit, maintain and train employees to use equipment must accompany PPE. Consult a competent industrial hygiene resource, the PPE manufacturer's recommendation, and/or applicable regulations to determine hazard potential and ensure adequate protection.

Eye/face protection:

Safety glasses. Chemical goggles under a full-face shield or respirator are

recommended if contact with liquefied gas is possible.

Skin Protection

Hand Protection: Wear protective gloves. Wear cold insulating gloves.

Skin and Body Protection:

Wear appropriate clothing to prevent any possibility of skin contact. Wear work clothes with long sleeves and pants. Fire resistant (i.e., Nomex) or natural fiber clothing (i.e., cotton or wool) is recommended. Synthetic clothing can generate static electricity and is not recommended where a flammable vapor release may occur. Wear chemical-resistant safety footwear with good traction to prevent slipping. Static Dissipative (SD) rated footwear is also recommended.

Respiratory Protection: Air supplied breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

Hygiene measures: Use effective control measures and PPE to maintain worker exposure to concentrations that are below these limits. Ensure that eyewash stations and safety showers are in close proximity to work locations.

9. Physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Faint hydrocarbon odor
Odor Threshold:	23 ppm (propylene), (detection)
pH:	not applicable
Melting point/freezing point:	-185 °C (-301 °F) (propylene)
Initial boiling point and boiling range:	-48 °C (-54 °F) (propylene)
Flash Point:	-108 °C (-162 °F) (Pensky-Martens Closed Cup)
Evaporation rate:	not applicable
Flammability (solid, gas):	Extremely flammable.
Upper/lower limit on flammability or explosive limits	
Flammability Limit - Upper (%):	11 %(V) (propylene)
Flammability Limit - Lower (%):	2 %(V) (propylene)
Vapor pressure:	10.3 atm (21 °C (70 °F)) (propylene)
Vapor density:	1.5 (0 °C (32 °F)) (Air=1)
Density:	530 kg/m ³
Relative density:	0.53 (0 °C (32 °F)) (propylene, liquefied) (Water=1)
Solubility(ies)	
Solubility in water:	(21 °C (70 °F)) Slightly Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	1.77
Auto-ignition temperature:	455 °C (851 °F)
Decomposition temperature:	No data available.
Viscosity:	not applicable

10. Stability and reactivity

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to heat.

Chemical Stability: Stable under normal conditions.

Possibility of hazardous reactions:	Under specific conditions, such as high temperature and pressure, and when product is in liquid state, product may polymerize with metal coordination complexes or mixtures of lithium nitrate and sulfur dioxide. May react vigorously with oxidizing agents. Liquefied gas may explode on contact with hot water (45 °C to 75 °C) (113 °F to 167 °F).
Conditions to avoid:	Keep away from heat, sparks and open flame.
Incompatible Materials:	Strong oxidizing agents. Nitrogen oxides. Nitrates. Perchlorates. Many materials become brittle after contact with liquefied gases and may fail without warning. Carefully select and test equipment, gaskets and hoses periodically to ensure integrity and compatibility.
Hazardous Decomposition Products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	Product is not acutely toxic.
Ingestion:	Ingestion of this product is not a likely route of exposure.
Skin Contact:	The liquefied form will cause freezing burns (frostbite).
Eye contact:	The liquefied form will cause freezing burns (frostbite).

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	Headache, dizziness, nausea, heartbeat irregularities.
Ingestion:	No adverse effects due to ingestion are expected.
Skin Contact:	Frostbite.
Eye contact:	Frostbite.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	Not classified for acute toxicity based on available data.
Dermal Product:	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.

Repeated dose toxicity Product: No data available.

Skin Corrosion/Irritation Product: No data available.

Components:	
Propane	Contact with liquid form may cause frostbite.
1-Propyne	Contact with the liquefied or pressurized gas may cause frostbite.

1,2-Propadiene	Contact with liquid form may cause frostbite.
1,3-Butadiene	Not likely, due to the form of the product. Frostbite hazard - rapidly expanding gas or liquid may cause frostbite.
Ethane	Not likely, due to the form of the product.

Serious Eye Damage/Eye Irritation

Product: No data available.

Components:

Propane	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.
1-Propyne	Contact with the liquefied or pressurized gas may cause momentary freezing followed by swelling and eye damage.
1,2-Propadiene	Contact with liquefied gas might cause frostbites, in some cases with tissue damage.
1,3-Butadiene	Irritant of eyes and mucous membranes. Frostbite hazard - rapidly expanding gas or liquid may cause frostbite.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

1,3-Butadiene Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

1,3-Butadiene Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

1,3-Butadiene Cancer

Germ Cell Mutagenicity**In vitro**

Product: May cause genetic defects.

In vivo

Product: May cause genetic defects.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Components:

1,3-Butadiene Liver, Blood, Lungs, ovaries, testes

Aspiration Hazard

Product: not applicable

Other effects:

Propylene that is inhaled is largely exhaled unchanged. A small fraction may be metabolized and transported in blood as propylene oxide. There is

no known health effect found to be associated with this metabolism in 2-year cancer studies or in studies of potential adverse genetic effects.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Components:

1,3-Butadiene LC 50 (96 h): 21.4 - 49.8 mg/l

Aquatic Invertebrates

Product: No data available.

Components:

1,3-Butadiene EC 50 (Water Flea, 48 h): 24.8 mg/l

Ethane LC 50 (Water Flea, 48 h): 46.6 mg/l
Ethane is not considered harmful to aquatic life.

Toxicity to Aquatic Plants

Product: No data available.

Components:

1,3-Butadiene EC 50 (Alga, 96 h): 11 - 33 mg/l

Ethane EC 50 (Alga, 96 h): 7.71 mg/l
Ethane is not considered harmful to aquatic life.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: 1.77

Mobility in soil: Low potential.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Waste generator is advised to carefully consider hazardous properties and control measures needed for other materials that may be found in the waste.

Contaminated Packaging: Check local, federal and state environmental regulations prior to disposal.

14. Transport information**DOT**

UN Number:	UN 1075
UN Proper Shipping Name:	Petroleum gases, liquefied
Shipping Name Continued:	(propylene) Not Odorized
Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
Packing Group:	–
Marine Pollutant:	No
Special precautions for user:	Reference Emergency Response Guidebook No. 115, latest revision.
Reportable quantity	1,3-Butadiene 10 lbs

15. Regulatory information**US Federal Regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
1,3-Butadiene	Eye irritation respiratory tract irritation Central nervous system Cancer Flammability

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Name on List:</u>	<u>Reportable quantity</u>
1,3-Butadiene	1,3-BUTADIENE	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Flammable (gases, aerosols, liquids, or solids), Gas under pressure, Germ Cell Mutagenicity, Carcinogenicity, Simple asphyxiant

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
1-Propene	10000 lbs	25000 lbs.
1,3-Butadiene	10000 lbs	25000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
1-Propene	10000 lbs
Propane	10000 lbs
1-Propyne	10000 lbs
1,2-Propadiene	10000 lbs
1,3-Butadiene	10000 lbs
Ethane	10000 lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

WARNING: This product can expose you to chemicals including, 1,3-Butadiene; which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.**US. New Jersey Worker and Community Right-to-Know Act**

<u>Chemical Identity</u>
1-Propene
Propane
1-Propyne
1,2-Propadiene
1,3-Butadiene

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u>
1-Propene
Propane
1-Propyne
1,3-Butadiene

Inventory Status

Canada DSL Inventory List: On or in compliance with the inventory

US TSCA Inventory: On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 02/13/2020

Revision Information: 02/13/2020: SDS Update

Version #: 9.0

Abbreviations and acronyms: ACC = American Chemistry Council; ACGIH = American Conference of Governmental Industrial Hygienists; BOD = Biochemical Oxygen Demand; C = Ceiling; CAS = Chemical Abstracts Service; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; COD = Chemical Oxygen Demand; DOT = Department of Transportation; DSL = Domestic Substances List; EC50 = Effective Concentration 50%; EPA =

Environmental Protection Agency; GHS = Globally Harmonized System for the Classification and Labelling of Chemicals; HPV = High Production Volume; IARC = International Agency for Research on Cancer; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit; PMCC = Pensky-Martens Closed Cup; PPE = Personal Protective Equipment; RCRA = Resource Conservation and Recovery Act; REL = Recommended Exposure Limit; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; SDS = Safety Data Sheet; STEL = Short Term Exposure Limit; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average

Further Information:

For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity".

Naturally Occurring Radioactive Material (NORM): This information is given to call attention to the issue of Naturally Occurring Radioactive Material (NORM) contamination. Industry experience has shown that this product may contain small amounts of Radon-222 (Rn-222) and its radioactive decay products.

Radon-222 is a naturally occurring radioactive gas that has been found to be a contaminant in natural gas. During processing, Rn-222 tends to be concentrated in the liquefied petroleum gas stream and in product streams having a similar boiling point range. Although Rn-222 levels in this product do not present any direct radon exposure, customers should be aware of the potential for buildup of Rn-222 decay products within their processing streams. The concentration of Rn-222 decay products in processing equipment (e.g. pumps, filters, piping, etc.) may accumulate to a point where gamma radiation is detected outside of this equipment during normal operations.

Field studies quoted in the literature, and those conducted by company personnel, have not shown any conditions, which subject workers to cumulative exposures that may exceed regulated limits. Equipment emitting gamma radiation should be presumed to be internally contaminated with alpha-emitting decay products (i.e. Lead-210, Polonium-210). These decay products may be a health hazard if inhaled or ingested. Equipment and piping should be checked for possible treatment (decontamination) prior to maintenance or disposal/salvage.

Protective equipment (e.g. coveralls, gloves, and a respirator with HEPA filters, or supplied air) should be worn by personnel entering a vessel or working on contaminated process equipment to prevent skin contamination, ingestion, or inhalation of any NORM contaminated residue. Airborne contamination may be minimized by handling contaminated materials in a wet state.

Disclaimer:

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, **NOVA CHEMICALS MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY NOVA CHEMICALS OR OTHERS IS TO BE INFERRED. THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT NOVA CHEMICALS FOR THE MOST CURRENT VERSION OF THIS SDS. NOVA CHEMICALS DOES NOT ASSUME RESPONSIBILITY FOR SDS OBTAINED FROM THIRD PARTY SOURCES.**

UNLESS SPECIFICALLY AGREED OTHERWISE, NOVA CHEMICALS DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL OF THE PRODUCT/MATERIALS DESCRIBED HEREIN.

is a registered trademark of NOVA Brands Ltd.; authorized use/utilisation autorisée.