

SAFETY DATA SHEET

Classified in accordance with Health Canada Hazardous Products Regulations (SOR/2015-17)

1. Identification

Product identifier: Gasoline Blendstock C6-C8**Other means of identification****Common name(s),** Blended Reformate/Raffinate**synonym(s):****SDS number:** NOVA-0021**Recommended use and restriction on use****Recommended use:** Gasoline blending or fuel products blending.**Restrictions on use:** All uses other than the identified.**Manufacturer/Importer/Supplier/Distributor Information****Manufacturer**

Company Name: NOVA Chemicals
Address: P.O. Box 2518, Station M
Calgary, Alberta, Canada T2P 5C6
Telephone: Product Information: 1-412-490-4063
SDS Information Email: msdsemail@novachem.com

Emergency telephone number:

1-800-561-6682, 1-403-314-8767 (NOVA Chemicals) (24 hours)

1-800-424-9300 (CHEMTREC) (24 hours)

2. Hazard(s) identification

Hazard Classification According to Hazardous Products Regulations**Physical Hazards**

Flammable liquids	Category 2
Physical Hazards Not Otherwise Classified (PHNOC) - Static-accumulating flammable liquid	Category 1

Health Hazards

Acute toxicity (Oral)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3
Specific Target Organ Toxicity - Repeated Exposure	Category 1
Specific Target Organ Toxicity - Repeated Exposure	Category 2
Aspiration Hazard	Category 1

Environmental Hazards

Acute hazards to the aquatic environment	Category 1
--	------------

Chronic hazards to the aquatic
environment

Category 1

Label Elements**Hazard Symbol:****Signal Word:**

Danger

Hazard Statement:

Highly flammable liquid and vapour.
Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.
Sparks may ignite liquid and vapour.
May cause flash fire or explosion.
Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.
(Blood)
(Nervous System)
May cause damage to organs through prolonged or repeated exposure.
(Hearing organs)
(Central nervous system)
May be fatal if swallowed and enters airways.
Very toxic to aquatic life with long lasting effects.

Precautionary Statements:**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapours. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. Avoid release to the environment.

Response:

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTRE. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF exposed or concerned: Get

medical attention. In case of fire: Use dry chemical, foam, carbon dioxide (CO₂), water spray or fog to extinguish. Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal: Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Cyclopentane, methyl-	Methylcyclopentane	96-37-7	10 - 25%
Cyclohexane	Benzene hexahydride	110-82-7	10 - 25%
Hexane	n-Hexane	110-54-3	2 - 25%
Cyclopentane	Pentamethylene	287-92-3	4 - 15%
4,7-Methano-1H-indene, 3a,4,5,6,7,7a-hexahydro-	Dihydrodicyclopentadiene	4488-57-7	0 - 12%
Octane	n-Octane	111-65-9	1 - 10%
Pentane, 2-methyl-	Isohexane	107-83-5	0 - 10%
Cyclohexane, methyl-	Methylcyclohexane	108-87-2	0 - 10%
Pentane	n-Pentane	109-66-0	0 - 5%
Heptane, 3-methyl-	3-Methylheptane	589-81-1	0 - 5%
Pentane, 3-methyl-	3-Methylpentane	96-14-0	0 - 5%
1-ethyl-1-methylcyclohexane	Cyclohexane, ethylmethyl-	4926-90-3	0 - 5%
Cyclohexane, ethyl-	Ethylcyclohexane	1678-91-7	0 - 5%
Hexane, 3-methyl-	3-Methylhexane	589-34-4	0 - 5%
Benzene, ethyl-	Ethylbenzene, Phenylethane	100-41-4	0.1 - 4%
Benzene, dimethyl-	Xylene (mixed isomers)	1330-20-7	0.1 - 3%
Cyclohexane, (1-methylethyl)-	Isopropylcyclohexane	696-29-7	0 - 3%
Pentane, 2,3-dimethyl-	2,3-Dimethylpentane	565-59-3	0 - 3%
Toluene	Methylbenzene	108-88-3	0.1 - 2%
Hexane, 2-methyl-	2-Methylhexane	591-76-4	0 - 2%
n-Undecane	Undecane	1120-21-4	0 - 2%
Benzene	Benzol	71-43-2	0 - 1.5%
Heptane	n-Heptane	142-82-5	0 - 1%
Nonane	n-Nonane	111-84-2	0 - 1%
Butane, 2-methyl-	2-Methylbutane, Isopentane	78-78-4	0 - 1%
Pentane, 2,4-dimethyl-	2,4-Dimethylpentane	108-08-7	0 - 1%
2,2-Dimethylpentane	Pentane, 2,2-dimethyl-	590-35-2	0 - 1%
3,3-Dimethylhexane	Hexane, 3,3-dimethyl-	563-16-6	0 - 1%
trans-1,2-Dimethylcyclohexane	Cyclohexane, 1,2-dimethyl-, trans-	6876-23-9	0 - 1%
2,2,3,4-Tetramethylpentane	Pentane, 2,2,3,4-tetramethyl-	1186-53-4	0 - 1%
Pentane, 3-ethyl-	3-Ethylpentane	617-78-7	0 - 0.5%
2-Methylheptane	Heptane, 2-methyl-	592-27-8	0 - 0.5%
Hexane, 3,4-dimethyl-	3,4-Dimethylhexane	583-48-2	0 - 0.2%
Hexane, 3-ethyl-	3-Ethylhexane	619-99-8	0 - 0.15%

* All concentrations are percent by weight.

Additional Information: This product has been assigned a CAS # of 68333-81-3 - Alkanes, C4-12. This product is considered hazardous by the Hazardous Products Regulations.

4. First-aid measures

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE if you feel unwell.

Ingestion: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTRE.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Skin irritation. Eye irritation. Respiratory irritation. Drowsiness. Dizziness. Blood disorders.

Indication of immediate medical attention and special treatment needed

Treatment: Ensure thorough eye and skin decontamination. Treat unconsciousness, nausea, hypotension, seizures and cardiac dysrhythmias in the conventional manner. This product may cause cardiac sensitization and dysrhythmia. Do not use mouth-to-mouth resuscitation if this liquid has been ingested or inhaled – use a proper respiratory medical device. Aspiration of this product during induced emesis can result in lung injury. If evacuation of stomach contents is considered necessary, use the method least likely to cause aspiration, such as gastric lavage after protecting the airway. Observe hospitalized patients for delayed chemical pneumonia, acute kidney failure, altered level of consciousness, and cardiac rhythm disturbances.

5. Fire-fighting measures

General Fire Hazards: Highly flammable liquid and vapour. Presence of strong oxidizers can increase fire and explosion hazard. Vapours are heavier than air and may travel to a source of ignition and flash back. Closed containers may rupture violently when heated. If tank, rail car or tank truck is involved in fire, ISOLATE for 800 metres (1/2 mile) in all directions; also, consider initial evacuation for 800 metres (1/2 mile) in all directions. Vapours may form explosive mixture with air. Keep containers away from source of heat or fire. This product may be a static accumulator which can form an ignitable vapour-air mixture in a storage tank.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use dry chemical, foam, carbon dioxide (CO₂), water spray or fog to extinguish. Use water to cool fire-exposed containers and to protect personnel.

Unsuitable extinguishing media: Do not use straight/direct streams as this may actually spread flames.

Specific hazards arising from the chemical: Upon combustion, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: Keep upwind. Keep unauthorized personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Immediately withdraw in case of fire and container venting or heat discoloration of a container. Avoid inhaling any smoke and combustion materials. Remove and isolate contaminated clothing and shoes. Cool containers with flooding quantities of water until well after the fire is out. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Reference Emergency Response Guidebook No. 128 for additional details and instructions.

Special protective equipment for fire-fighters: Wear positive pressure self-contained breathing apparatus (SCBA). Structural fire-fighters' protective clothing provides thermal protection **but only limited chemical protection**.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear appropriate personal protective equipment. Isolate area. Keep unauthorized personnel away. Alert stand-by emergency and fire-fighting personnel. Monitor surrounding area for buildup of flammable concentrations in air.

Methods and material for containment and cleaning up: Do not touch or walk through spilled material. In case of leakage, eliminate all ignition sources. As an immediate precautionary measure, isolate spill or leak area for at least 50 metres (164 feet) in all directions. All equipment used when handling the product must be grounded. Keep upwind. Keep out of low areas. Stop leak if safe to do so. Contain discharge by booming on water or diking on ground. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

Small Spills: Remove liquid material with non-sparking approved pumps, skimmers or vacuum equipment. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Use non-sparking tools.

Large Spills: Consider downwind evacuation for 300 metres (1000 feet). Spills on water will volatilize rapidly, making containment or recovery difficult. A vapour-suppressing foam may be used to reduce vapours. Remove pooled liquid material with approved, non-sparking pumps, skimmers or vacuum equipment. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Soil remediation may be required.

7. Handling and storage

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. These alone may be insufficient to remove static electricity. For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray

Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity". For additional information on storing and handling flammable liquids, refer to the National Fire Protection Association (NFPA) 30, "Flammable and Combustible Liquids Code". Take special precautions when cold cutting or breaking into lines, or when cleaning and disposing of empty containers. Parts and equipment should be steam cleaned prior to maintenance procedures. Do not breathe vapours. Avoid contact with skin and eyes. Keep away from incompatible materials such as oxidizing agents and acids. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. In case of inadequate ventilation, use respiratory protection. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities:

Storage area should be clearly identified, well-illuminated and clear of obstruction. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Only allow access to authorized persons. Store and handle in properly designed pressure vessels and equipment. Store and use away from heat, sparks, open flame, or any other ignition source. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Have appropriate extinguishing capability in storage area (e.g. sprinkler system, portable fire extinguishers) and flammable gas detectors. Keep absorbents for leaks and spills readily available. Inspect vents during winter conditions for vapour ice buildup. Storage tanks should be above ground and diked to hold entire contents. Store away from incompatible materials. Store according to applicable regulations and standards for flammable materials.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values		Source
Cyclohexane	TWA	100 ppm	344 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Cyclohexane	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Cyclohexane	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Cyclohexane	TWA	100 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
Cyclohexane	REL	300 ppm	1,050 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Cyclohexane	IDLH	1,300 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Hexane	TWA	50 ppm	176 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Hexane	TWA	20 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Hexane	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Hexane	TWA	50 ppm	176 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

Hexane	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
Hexane	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Hexane	IDLH	1,100 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Cyclopentane	TWA	600 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Cyclopentane	TWA	600 ppm	1,720 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Cyclopentane	TWA	600 ppm	1,720 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Cyclopentane	TWA	600 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Cyclopentane	REL	600 ppm	1,720 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Cyclopentane	TWA	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Octane	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Octane	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Octane	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Octane	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Octane	Ceil_Time	385 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Octane	REL	75 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Octane	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Octane	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended
Pentane, 2-methyl-	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane, 2-methyl-	STEL	1,000 ppm	3,500 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	500 ppm	1,760 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Pentane, 2-methyl-	TWA	500 ppm	1,760 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	STEL	1,000 ppm	3,500 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Pentane, 2-methyl-	TWA	200 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane, 2-methyl-	Ceil_Time	510 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane, 2-methyl-	REL	100 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane, 2-methyl-	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Cyclohexane, methyl-	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended

Cyclohexane, methyl-	TWA	400 ppm	1,610 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Cyclohexane, methyl-	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Cyclohexane, methyl-	TWA	400 ppm	1,610 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Cyclohexane, methyl-	IDLH	1,200 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Cyclohexane, methyl-	REL	400 ppm	1,600 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Cyclohexane, methyl-	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
Pentane	TWA	600 ppm	1,770 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Pentane	TWA	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane	TWA	1,000 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Pentane	TWA	1,000 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane	REL	120 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane	Ceil_Time	610 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane	IDLH	1,500 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Pentane	TWA	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Heptane, 3-methyl-	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Heptane, 3-methyl-	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Heptane, 3-methyl-	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Heptane, 3-methyl-	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Heptane, 3-methyl-	REL	75 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Heptane, 3-methyl-	Ceil_Time	385 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Heptane, 3-methyl-	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Heptane, 3-methyl-	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended
Pentane, 3-methyl-	TWA	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane, 3-methyl-	STEL	1,000 ppm	3,500 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	500 ppm	1,760 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Pentane, 3-methyl-	TWA	500 ppm	1,760 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	STEL	1,000 ppm	3,500 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Pentane, 3-methyl-	TWA	200 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane, 3-methyl-	Ceil_Time	510 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane, 3-methyl-	REL	100 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Pentane, 3-methyl-	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Hexane, 3-methyl-	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	400 ppm	1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Hexane, 3-methyl-	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Hexane, 3-methyl-	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Hexane, 3-methyl-	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Hexane, 3-methyl-	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, ethyl-	STEL	125 ppm	543 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Benzene, ethyl-	TWA	20 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Benzene, ethyl-	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Benzene, ethyl-	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Benzene, ethyl-	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, ethyl-	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, ethyl-	IDLH	800 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Benzene, dimethyl-	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Benzene, dimethyl-	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Benzene, dimethyl-	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Benzene, dimethyl-	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Benzene, dimethyl-	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, dimethyl-	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene, dimethyl-	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Pentane, 2,3-dimethyl-	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	400 ppm	1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Pentane, 2,3-dimethyl-	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane, 2,3-dimethyl-	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Pentane, 2,3-dimethyl-	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane, 2,3-dimethyl-	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Toluene	TWA	20 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Toluene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Toluene	TWA	50 ppm	188 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Toluene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Toluene	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Toluene	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Toluene	IDLH	500 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Hexane, 2-methyl-	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

	TWA	400 ppm	1,640 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Hexane, 2-methyl-	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Hexane, 2-methyl-	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Hexane, 2-methyl-	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Hexane, 2-methyl-	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene	STEL	2.5 ppm	8 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	0.5 ppm	1.6 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	TWA	0.5 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Benzene	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Benzene	TWA	1 ppm	3 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	STEL	5 ppm	15.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Benzene	IDLH	500 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Benzene	TWA	0.02 ppm		US. ACGIH Threshold Limit Values, as amended
Heptane	TWA	400 ppm	1,640 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	STEL	500 ppm	2,050 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Heptane	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Heptane	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Heptane	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Heptane	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Heptane	Ceil_Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Heptane	IDLH	750 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Heptane	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Nonane	TWA	200 ppm	1,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Nonane	TWA	200 ppm	1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Nonane	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Nonane	TWA	200 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Nonane	REL	200 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
Butane, 2-methyl-	TWA	600 ppm	1,770 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Butane, 2-methyl-	TWA	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Butane, 2-methyl-	TWA	1,000 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Butane, 2-methyl-	TWA	1,000 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Butane, 2-methyl-	TWA	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Pentane, 2,4-dimethyl-	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	400 ppm	1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Pentane, 2,4-dimethyl-	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane, 2,4-dimethyl-	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Pentane, 2,4-dimethyl-	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended

	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane, 2,4-dimethyl-	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
2,2,3,4-Tetramethylpentane	TWA	200 ppm	1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
2,2,3,4-Tetramethylpentane	TWA	200 ppm	1,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
2,2,3,4-Tetramethylpentane	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
2,2,3,4-Tetramethylpentane	TWA	200 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
2,2,3,4-Tetramethylpentane	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
2,2,3,4-Tetramethylpentane	REL	200 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
2,2-Dimethylpentane	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	TWA	400 ppm	1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
2,2-Dimethylpentane	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
2,2-Dimethylpentane	STEL	500 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
	TWA	400 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
2,2-Dimethylpentane	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
2,2-Dimethylpentane	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
3,3-Dimethylhexane	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
3,3-Dimethylhexane	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
3,3-Dimethylhexane	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
3,3-Dimethylhexane	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
3,3-Dimethylhexane	REL	75 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
3,3-Dimethylhexane	Ceil_Time	385 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
3,3-Dimethylhexane	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
3,3-Dimethylhexane	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended

Pentane, 3-ethyl-	TWA	400 ppm	1,640 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	STEL	500 ppm	2,050 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Pentane, 3-ethyl-	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	TWA	400 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Pentane, 3-ethyl-	TWA	400 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	STEL	500 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Pentane, 3-ethyl-	STEL	400 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	200 ppm		US. ACGIH Threshold Limit Values, as amended
2-Methylheptane	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
2-Methylheptane	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
2-Methylheptane	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
2-Methylheptane	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
2-Methylheptane	REL	75 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
2-Methylheptane	Ceil_Time	385 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
2-Methylheptane	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
2-Methylheptane	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended
Hexane, 3,4-dimethyl-	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Hexane, 3,4-dimethyl-	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Hexane, 3,4-dimethyl-	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Hexane, 3,4-dimethyl-	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Hexane, 3,4-dimethyl-	REL	75 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Hexane, 3,4-dimethyl-	Ceil_Time	385 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Hexane, 3,4-dimethyl-	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Hexane, 3,4-dimethyl-	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended
Hexane, 3-ethyl-	TWA	300 ppm	1,400 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Hexane, 3-ethyl-	TWA	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Hexane, 3-ethyl-	TWA	300 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

Hexane, 3-ethyl-	TWA	300 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
Hexane, 3-ethyl-	REL	75 ppm	350 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Hexane, 3-ethyl-	Ceiling	385 ppm	1,800 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Hexane, 3-ethyl-	IDLH	1,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
Hexane, 3-ethyl-	TWA	300 ppm		US. ACGIH Threshold Limit Values, as amended

Please refer to the latest edition of the appropriate source text and consult an industrial hygienist or similar professional, or local agencies, for further information.

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Cyclohexane (1,2-Cyclohexanediol, with hydrolysis: Sampling time: End of shift at end of work week.)	50 mg/g (Creatinine in urine)	ACGIH BEI
Hexane (2,5-Hexanedione, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEI
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	150 mg/g (Creatinine in urine)	ACGIH BEI
Benzene, dimethyl- (Methylhippuric acids: Sampling time: End of shift.)	0.3 g/g (Creatinine in urine)	ACGIH BEI
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEI
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEI
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEI
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEI
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEI

Exposure guidelines

Chemical Identity	Notations	Source
Hexane	Can be absorbed through the skin.	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
	Can be absorbed through the skin.	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	Can be absorbed through the skin.	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
	Can be absorbed through the skin.	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended
Toluene	Can be absorbed through the skin.	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
Benzene	Can be absorbed through the skin.	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

	Can be absorbed through the skin.	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended
	Can be absorbed through the skin.	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Appropriate Engineering Controls

Engineering methods to reduce hazardous exposure are preferred controls. Methods include mechanical ventilation (dilution and local exhaust) process or personal enclosure, remote and automated operation, control of process conditions, leak detection and repair systems, and other process modifications. Ensure all exhaust ventilation systems are discharged to outdoors, away from air intakes and ignition sources. Supply sufficient replacement air to make up for air removed by exhaust systems. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Administrative (procedure) controls and use of personal protective equipment may also be required.

Individual protection measures, such as personal protective equipment (PPE)

General information: Personal protective equipment (PPE) should not be considered a long-term solution to exposure control. Employer programs to properly select, fit, maintain and train employees to use equipment must accompany PPE. Consult a competent industrial hygiene resource, the PPE manufacturer's recommendation, and/or applicable regulations to determine hazard potential and ensure adequate protection.

Eye/face protection: Safety glasses. Chemical goggles are recommended if splashing is possible or to prevent eye irritation from vapours.

Skin Protection

Hand Protection: Chemical resistant gloves.

Skin and Body Protection: Wear appropriate clothing to prevent any possibility of skin contact. Wear work clothes with long sleeves and pants. If splashing or contact with liquid material is possible, consider the need for an impervious overcoat. Fire resistant (i.e., Nomex) or natural fibre clothing (i.e., cotton or wool) is recommended. Synthetic clothing can generate static electricity and is not recommended where a flammable vapour release may occur. Wear chemical-resistant safety footwear with good traction to prevent slipping. Static Dissipative (SD) rated footwear is also recommended.

Respiratory Protection: Appropriate NIOSH approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4, or self-contained breathing apparatus should be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators or IDLH levels.

Hygiene measures: Use effective control measures and PPE to maintain worker exposure to concentrations that are below these limits. Ensure that eyewash stations and safety showers are in close proximity to work locations.

9. Physical and chemical properties**Appearance**

Physical state:	liquid
Form:	liquid
Colour:	Colourless
Odour:	sweet aromatic
Odour Threshold:	No data available.

Melting point/freezing point:	-160 °C (-256 °F) (estimated)
Initial boiling point and boiling range:	40 - 190 °C (104 - 374 °F)
Flammability (solid, gas):	not applicable
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower(%):	No data available.
Flash Point:	< -18 °C (< -0.40 °F) (Closed cup)
Auto-ignition temperature:	254 °C (489 °F)
Decomposition temperature:	No data available.
pH:	not applicable
Kinematic viscosity:	2 mm ² /s (40 °C (104 °F)), estimated
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	Highly soluble in ether, alcohols and other aliphatic solvents.
Partition coefficient (n-octanol/water):	2.2 - 4.5 (similar mixtures)
Vapour pressure:	27 - 43 kPa (37.8 °C (100.0 °F)) (Reid Vapour Pressure)
Evaporation rate:	5.6
Density:	720 - 780 kg/m ³
Relative density:	0.72 - 0.78 (Water=1)
Vapour density:	3 (Air=1) (ambient conditions)
Particle characteristics	
Particle Size:	not applicable
Other information	
Explosive properties:	No data available.

10. Stability and reactivity

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Chemical Stability:	Stable under normal storage conditions. Some components of the product become unstable at elevated temperatures and pressures.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Incompatible Materials:	Oxidizers. Presence of strong oxidizers can increase fire and explosion hazard.
Hazardous Decomposition Products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	Inhalation of this product causes headache, dizziness and nausea and loss of coordination. Repeated inhalation may result in bronchitis or other breathing problems, possible damage to the peripheral nervous systems and possible cardiac sensitization. Minute amounts aspirated into the lungs
--------------------	--

during ingestion or vomiting may cause pulmonary injury.

Ingestion: Harmful if swallowed. Minute amounts aspirated into the lungs during ingestion or vomiting may cause severe pulmonary injury. Ingestion of this product may result in vomiting, nausea, abdominal pain and central nervous system effects including headache, sleepiness, dizziness and nausea. Ingestion may also cause blood disorders.

Skin Contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Central nervous system (hearing effect). Respiratory irritation.

Ingestion: Vomiting, nausea, abdominal pain and central nervous system effects including headache.

Skin Contact: Skin irritation.

Eye contact: Eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 1,091 mg/kg
Harmful if swallowed.

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Components:

Benzene
LOAEL (Rat, Oral): 25 mg/kg (Target Organ(s): Blood)
LOAEL (Rat, Inhalation - vapour): 0.958 mg/l (Target Organ(s): Blood)
LOAEL (Human, Inhalation - vapour): 0.0018 mg/l (Target Organ(s): Blood)

Skin Corrosion/Irritation

Product: Causes skin irritation.

Serious Eye Damage/Eye Irritation

Product: Causes serious eye irritation.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Benzene, ethyl- Overall evaluation: 2B. Possibly carcinogenic to humans.
Benzene Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Benzene Known To Be Human Carcinogen.

ACGIH Carcinogen List:Benzene, ethyl- Group A3: Confirmed animal carcinogen with unknown relevance to humans.
Benzene Group A1: Confirmed human carcinogen.**Germ Cell Mutagenicity****In vitro****Product:** May cause genetic defects.**In vivo****Product:** May cause genetic defects.**Reproductive toxicity****Product:** Suspected of damaging fertility or the unborn child.**Specific Target Organ Toxicity - Single Exposure****Product:** May cause respiratory irritation. May cause drowsiness or dizziness.**Specific Target Organ Toxicity - Repeated Exposure****Product:** Blood, Nervous system - Causes damage to organs through prolonged or repeated exposure.

Central nervous system, hearing organs - May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard**Product:** May be fatal if swallowed and enters airways.**Other effects:**

Xylene is a developmental toxicant in Canada.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** Very toxic to aquatic life.**Aquatic Invertebrates****Product:** Very toxic to aquatic life.**Toxicity to aquatic plants****Product:** Very toxic to aquatic life.**Chronic hazards to the aquatic environment:****Fish****Product:** Very toxic to aquatic life with long lasting effects.**Aquatic Invertebrates****Product:** Very toxic to aquatic life with long lasting effects.**Toxicity to aquatic plants****Product:** Very toxic to aquatic life with long lasting effects.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: 2.2 - 4.5 (similar mixtures)

Mobility in Soil: When released into the environment, this product is expected to partition primarily to air (> 95%), with some partitioning to water (< 3%), to soils (< 2%) and into sediment (< 1%). Spill remediation has shown potential for downward movement and partitioning into groundwater.

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of contents and container in accordance with local regulations. Waste generator is advised to carefully consider hazardous properties and control measures needed for other materials that may be found in the waste.

Contaminated Packaging: Check local, federal and provincial environmental regulations prior to disposal.

14. Transport information**TDG**

UN number or ID number: UN 1268
UN Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S.
Class: 3
Packing Group: II
Label(s): 3
Special precautions for user: Reference Emergency Response Guidebook No. 128, latest revision.

IMDG

UN number or ID number: UN 1268
UN Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S.
Transport Hazard Class(es)
Class: 3
Label(s): 3
EmS No.: F-E, S-E
Packing Group: II
Marine pollutant: Yes
Limited quantity: 1.00L
Excepted quantity: E2
Special precautions for user: Transport in bulk according to IMO instruments

15. Regulatory information**Canada Federal Regulations****List of Toxic Substances (CEPA, Schedule 1)****Chemical Identity**

Benzene

Name on List:

Benzene

Export Control List (CEPA 1999, Schedule 3)

Not regulated

Greenhouse Gases

Not regulated

Precursor Control Regulations**Chemical Identity**

Toluene

Canada. Substances Subject to Significant New Activity (SNAc) Reporting Requirements (CEPA section 81), as amended

Not regulated

Inventory status

Canada DSL Inventory List: On or in compliance with the inventory

US TSCA Inventory: On or in compliance with the inventory

16. Other information, including date of preparation or last revision**Issue Date:** 02/19/2026**Revision Information:** 02/19/2026: SDS Update – GHS classification change, phrase edits**Version #:** 8.0

Abbreviations and acronyms: ACGIH = American Conference of Governmental Industrial Hygienists; BOD = Biochemical Oxygen Demand; CAS = Chemical Abstracts Service; CEPA = Canadian Environmental Protection Act; COD = Chemical Oxygen Demand; DSL = Domestic Substances List; EC50 = Effective Concentration 50%; EPA = Environmental Protection Agency; GHS = Globally Harmonized System for the Classification and Labelling of Chemicals; IARC = International Agency for Research on Cancer; IDLH = Immediately Dangerous to Life or Health; Kow = Octanol/water partition coefficient; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; LEL = Lower Explosive Limit; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OEL = Occupational Exposure Limit; OSHA = Occupational Safety and Health Administration; PNOC = Particulates Not Otherwise Classified; PPE = Personal Protective Equipment; REL = Recommended Exposure Limit; SCBA = Self Contained Breathing Apparatus; SDS = Safety Data Sheet; STEL = Short Term Exposure Limit; TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average

Further Information: For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity".

For additional information on storing and handling flammable liquids, refer to the National Fire Protection Association (NFPA) 30, "Flammable and Combustible Liquids Code".

Disclaimer: ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE

TIME OF PREPARATION OF THIS DOCUMENT, NOVA CHEMICALS MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY NOVA CHEMICALS OR OTHERS IS TO BE INFERRED. THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT NOVA CHEMICALS FOR THE MOST CURRENT VERSION OF THIS SDS. NOVA CHEMICALS DOES NOT ASSUME RESPONSIBILITY FOR SDS OBTAINED FROM THIRD PARTY SOURCES.

UNLESS SPECIFICALLY AGREED OTHERWISE, NOVA CHEMICALS DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL OF THE PRODUCT/MATERIALS DESCRIBED HEREIN.



is a registered trademark of NOVA Brands Ltd.; authorized use/utilisation autorisée.