

# SAFETY DATA SHEET

Classified in accordance with Health Canada Hazardous Products Regulations (SOR/2015-17)

## 1. Identification

**Product identifier:** Mixed C4 Product**Other means of identification****Common name(s),  
synonym(s):** Crude C4's; Dilute Butadiene; Corunna Mixed C4's  
**SDS number:** NOVA-0014**Recommended use and restriction on use****Recommended use:** Raw material used in industrial applications for chemical and elastomers manufacturing.**Restrictions on use:** All uses other than the identified.**Manufacturer/Importer/Supplier/Distributor Information****Manufacturer****Company Name:** NOVA Chemicals  
**Address:** P.O. Box 2518, Station M  
Calgary, Alberta, Canada T2P 5C6  
**Telephone:** Product Information: 1-412-490-4063  
**SDS Information Email:** [msdsemail@novachem.com](mailto:msdsemail@novachem.com)**Emergency telephone number:**

1-800-561-6682, 1-403-314-8767 (NOVA Chemicals) (24 hours)

## 2. Hazard(s) identification

**Hazard Classification According to Hazardous Products Regulations****Physical Hazards**

Flammable gas	Category 1
Gases under pressure	Liquefied gas

**Health Hazards**

Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

**Environmental Hazards**

Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3

**Label Elements****Hazard Symbol:****Signal Word:**

Danger

**Hazard Statement:** Extremely flammable gas.  
Contains gas under pressure; may explode if heated.  
May cause genetic defects.  
May cause cancer.  
Harmful to aquatic life with long lasting effects.

**Precautionary Statements:**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** IF exposed or concerned: Get medical advice/attention. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources.

**Storage:** Store locked up. Protect from sunlight. Store in a well-ventilated place.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** Contact with liquefied gas may cause irritation and/or frostbite.

### 3. Composition/information on ingredients

**Mixtures**

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
1,3-Butadiene	Vinylethylene	106-99-0	50 - 75%
n-Butane	Butane	106-97-8	10 - 30%
1-Butene	Butene-1	106-98-9	8 - 14%
2-Butene	Butylene	107-01-7	5 - 7%
1-Propene, 2-methyl-	Iso-butene, Isobutylene	115-11-7	1 - 5%
Propane, 2-methyl-	Isobutane	75-28-5	1 - 5%
1,2-Butadiene	Buta-1,2-diene	590-19-2	0.1 - 0.5%
Propane, 2,2-dimethyl-	Neopentane	463-82-1	0.01 - 0.2%
Cyclopropane, methyl-	Methylcyclopropane	594-11-6	0.01 - 0.1%

\* All concentrations are percent by weight.

**Additional Information:** This product has been assigned a CAS # of 68476-52-8 - Hydrocarbons, C4, ethylene-manuf.-by-product. It is comprised of the above listed components. This product is considered hazardous by the Hazardous Products Regulations, 2015.

### 4. First-aid measures

**Inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Seek medical attention.

**Ingestion:** Ingestion of this product is not a likely route of exposure. Do NOT induce vomiting. Seek medical attention.

<b>Skin Contact:</b>	Contact with liquefied gas may cause irritation and/or frostbite. Seek medical attention immediately in the event of frostbite. IF ON SKIN: Wash with plenty of soap and water. Thaw frosted parts with lukewarm water. Do not rub affected area. Remove non-adhering contaminated clothing. Do not remove adherent material or clothing. Seek medical attention.
<b>Eye contact:</b>	Contact with liquefied gas may cause irritation and/or frostbite. Seek medical attention immediately in the event of frostbite. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

**Most important symptoms/effects, acute and delayed**

**Symptoms:** Frostbite, headache, dizziness, nausea, heartbeat irregularities.

**Indication of immediate medical attention and special treatment needed**

**Treatment:** For more detailed medical emergency support information, call 1-800-561-6682 or 1-403-314-8767 (24 hours, NOVA Chemicals Emergency Response). Treat unconsciousness, frostbite, nausea, hypotension, seizures and cardiac arrhythmias in the conventional manner. Sympathomimetics or catecholamines should be avoided or used with caution (lowest effective dose) because of possible cardiac sensitization. Administer oxygen by mask if there is respiratory distress.

**5. Fire-fighting measures**

**General Fire Hazards:** Extremely flammable liquefied gas. Vapours may travel considerable distance to a source of ignition and flash back. DO NOT ATTEMPT TO EXTINGUISH A GAS FIRE UNLESS LEAK SOURCE CAN BE ISOLATED AND SHUT OFF. Be aware of possibility of reignition. Vapours may form explosive mixture with air. Consider need for immediate emergency isolation and evacuation. If a pipeline or a storage vessel is involved in a fire, ISOLATE for 1600 metres (1 mile) in all directions. Keep containers away from source of heat or fire. Contains gas under pressure; may explode if heated.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use dry chemical, foam, carbon dioxide (CO<sub>2</sub>), water spray or fog to extinguish. Use water to cool fire-exposed containers and to protect personnel.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Upon combustion, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** Keep upwind. Keep unauthorized personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Immediately withdraw in case of fire and container venting or heat discolouration of a container. Let uncontrolled fires burn off. Avoid inhaling any smoke and combustion materials. Remove and isolate contaminated clothing and shoes. Cool containers with flooding quantities of water until well after the fire is out. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Reference Emergency Response Guidebook No. 116P for additional details and instructions.

**Special protective equipment for firefighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unauthorized personnel away. Alert stand-by emergency and fire fighting personnel. Monitor surrounding area for buildup of flammable concentrations in air.

**Methods and material for containment and cleaning up:** Wear appropriate personal protective equipment. Do not touch or walk through spilled material. Eliminate all ignition sources if safe to do so. Keep upwind. Keep out of low areas. Stop leak if safe to do so. All equipment used when handling the product must be grounded. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Keep area isolated until any detectable flammable gas has been fully dispersed.

Small Spills: Isolate spill or leak area for 50 to 100 metres (164 to 330 feet).

Large Spills: Consider initial downwind evacuation for at least 800 metres (1/2 mile). Evacuate personnel to upwind of the spill area, and position at a safe distance. Use water spray to reduce gas or divert gas cloud drift. Soil remediation may be required.

## 7. Handling and storage

**Precautions for safe handling:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity". Procedures and design should exclude oxygen from the handling and processing systems. Take special precautions when cold cutting or breaking into lines, or when cleaning and disposing of empty containers. There is a potential for fire if fine metals such as packing is used. Equipment and piping should be checked for possible treatment (decontamination) prior to maintenance or disposal/salvage. Equipment preparation may include nitrogen purge, acid wash (to remove iron oxides), sodium nitrate pacification, and final oxygen removal using diethylhydroxylamine (DEHA) or other suitable materials. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Conditions for safe storage, including any incompatibilities:** Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Only allow access to authorized persons. Store and handle in properly designed pressure vessels and equipment. Store and use away from heat, sparks, open flame, or any other ignition source. Have appropriate extinguishing capability in storage area (e.g. sprinkler system, portable fire extinguishers) and flammable gas detectors. Storage pressure vessels should be above ground and diked. Store away from incompatible materials. Store according to applicable regulations and standards for flammable materials.

For road, rail and marine shipments, ensure product is transported with the addition of a suitable inhibitor / stabilizer, such as t-butyl catechol (TBC) or equivalent. Consider addition of TBC or equivalent to storage system if it cannot be maintained entirely free of oxygen.

**8. Exposure controls/personal protection****Control Parameters****Occupational Exposure Limits**

In the ACGIH TLVs® and BEIs® book, n-butane (CAS# 106-97-8) (as Butane, isomers) and Propane, 2-methyl- (as Butane, isomers) (CAS# 75-28-5) have been identified as being an "Explosion hazard". Please refer to the ACGIH TLVs® and BEIs® book, latest edition, for additional information.

Chemical Identity	type	Exposure Limit Values		Source
1,3-Butadiene	TWA	2 ppm	4.4 mg/m <sup>3</sup>	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
1,3-Butadiene	TWA	2 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
1,3-Butadiene	TWA	2 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
1,3-Butadiene	TWA	2 ppm	4.4 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended
1,3-Butadiene	TWA	2 ppm		US. ACGIH Threshold Limit Values, as amended
1,3-Butadiene	IDLH	2,000 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
n-Butane	TWA	1,000 ppm		Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended
n-Butane	TWA	800 ppm	1,900 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended
n-Butane	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
n-Butane	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
n-Butane	REL	800 ppm	1,900 mg/m <sup>3</sup>	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
n-Butane	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
n-Butane	IDLH	1,600 ppm		US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended
1-Butene	TWA	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
1-Butene	TWA	250 ppm		US. ACGIH Threshold Limit Values, as amended
2-Butene	TWA	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
2-Butene	TWA	250 ppm		US. ACGIH Threshold Limit Values, as amended
1-Propene, 2-methyl-	TWA	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
1-Propene, 2-methyl-	TWA	250 ppm		US. ACGIH Threshold Limit Values, as amended
Propane, 2-methyl-	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Propane, 2-methyl-	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
Propane, 2-methyl-	REL	800 ppm	1,900 mg/m <sup>3</sup>	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Propane, 2-methyl-	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended
Propane, 2,2-dimethyl-	TWA	600 ppm	1,770 mg/m <sup>3</sup>	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Propane, 2,2-dimethyl-	TWA	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended
Propane, 2,2-dimethyl-	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)
Propane, 2,2-dimethyl-	TWA	1,000 ppm	US. ACGIH Threshold Limit Values, as amended

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
1,3-Butadiene (1,2-Dihydroxy-4-(N-acetylcysteinyl)-butane: Sampling time: End of shift.)	2.5 mg/l (Urine)	ACGIH BEI
1,3-Butadiene (Mixture of N-1- and N-2-(hydroxybutenyl)valine hemoglobin (Hb) adducts: Sampling time: Not critical.)	2.5 pmol/g (Blood)	ACGIH BEI

### Appropriate Engineering Controls

Engineering methods to reduce hazardous exposure are preferred controls. Methods include mechanical ventilation (dilution and local exhaust) process or personal enclosure, remote and automated operation, control of process conditions, leak detection and repair systems, and other process modifications. Ensure all exhaust ventilation systems are discharged to outdoors, away from air intakes and ignition sources. Supply sufficient replacement air to make up for air removed by exhaust systems. Administrative (procedure) controls and use of personal protective equipment may also be required.

### Individual protection measures, such as personal protective equipment

**General information:** Personal protective equipment (PPE) should not be considered a long-term solution to exposure control. Employer programs to properly select, fit, maintain and train employees to use equipment must accompany PPE. Consult a competent industrial hygiene resource, the PPE manufacturer's recommendation, and/or applicable regulations to determine hazard potential and ensure adequate protection.

**Eye/face protection:** Safety glasses. Chemical goggles under a full-face shield are recommended if contact with liquefied gas is possible.

#### Skin Protection

**Hand Protection:** Wear protective gloves. Wear cold insulating gloves.

**Skin and Body Protection:** Wear appropriate clothing to prevent any possibility of skin contact. Wear work clothes with long sleeves and pants. Fire resistant (i.e., Nomex) or natural fibre clothing (i.e., cotton or wool) is recommended. Synthetic clothing can generate static electricity and is not recommended where a flammable vapour release may occur. Wear chemical-resistant safety footwear with good traction to prevent slipping. Static Dissipative (SD) rated footwear is also recommended.

**Respiratory Protection:** Appropriate NIOSH approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4, or self-contained breathing apparatus should be used. Air supplied breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

**Hygiene measures:** Use effective control measures and PPE to maintain worker exposure to concentrations that are below these limits. Ensure that eyewash stations and safety showers are in close proximity to work locations.



**9. Physical and chemical properties****Appearance**

<b>Physical state:</b>	Gas
<b>Form:</b>	Stabilized. Liquefied gas
<b>Colour:</b>	Colourless
<b>Odour:</b>	Faint aromatic odour
<b>Odour Threshold:</b>	0.45 ppm (detectable), (1,3-butadiene)
<b>pH:</b>	not applicable
<b>Melting point/freezing point:</b>	-108.9 °C (-164.0 °F) (1,3-butadiene)
<b>Initial boiling point and boiling range:</b>	-12 - 4 °C (10 - 39 °F)
<b>Flash Point:</b>	-76 °C (-105 °F) (Closed cup) (1,3-butadiene)
<b>Evaporation rate:</b>	not applicable
<b>Flammability (solid, gas):</b>	Extremely flammable.
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	11.5 %(V) (1,3-butadiene)
<b>Flammability limit - lower(%):</b>	2 %(V) (1,3-butadiene)
<b>Vapour pressure:</b>	2 atm (15.3 °C (59.5 °F)) (1,3-butadiene)
<b>Vapour density:</b>	1.9 (1,3-butadiene)
<b>Density:</b>	600 - 640 kg/m <sup>3</sup>
<b>Relative density:</b>	0.60 - 0.61 (calculated) (Water=1)
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	735 mg/l (1,3-butadiene)
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	1.99 (1,3-butadiene)
<b>Auto-ignition temperature:</b>	414 °C (777 °F) (1,3-butadiene)
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	not applicable

**10. Stability and reactivity**

<b>Reactivity:</b>	Product may become self-reactive under conditions of shock or increased temperature or pressure. In the presence of air, explosive peroxides and/or pyrophoric polymers may be produced. Procedures and design should exclude oxygen from the handling and processing systems, including removing oxygen before introducing the product. May form acetylides with copper, silver, mercury or alloys that are explosive and very hazardous when dry. Contact with incompatible materials. Sources of ignition. Exposure to heat.
<b>Chemical Stability:</b>	This product is <b>unstable</b> . Product may undergo vigorous polymerization in contact with air.
<b>Possibility of Hazardous Reactions:</b>	This product may undergo dangerous decomposition, condensation or polymerization. It may become self-reactive under conditions of shock or increased temperature or pressure. In the presence of air, explosive peroxides and/or pyrophoric polymers may be produced. May form acetylides with copper, silver, mercury or alloys that are explosive and very hazardous when dry. Hazardous polymerization can occur. Storage and processing requires review of risks and use of suitable inhibitors such as tert-butyl catechol (TBC) or equivalent. Liquefied gas may explode on contact with hot water (45 °C to 75 °C) (113 °F to 167 °F).
<b>Conditions to Avoid:</b>	Keep away from heat, sparks and open flame. Contact with incompatible materials.

<b>Incompatible Materials:</b>	Oxidizing agents. Organic compounds. Acids. Copper-containing alloys. Certain plastics and rubbers. Many materials become brittle after contact with liquefied gases and may fail without warning. Carefully select and test equipment, gaskets and hoses periodically to ensure integrity and compatibility.
<b>Hazardous Decomposition Products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide, low molecular weight hydrocarbons.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	Product is not acutely toxic.
<b>Ingestion:</b>	Ingestion of this product is not a likely route of exposure.
<b>Skin Contact:</b>	The liquefied form will cause freezing burns (frostbite).
<b>Eye contact:</b>	The liquefied form will cause freezing burns (frostbite).

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation:</b>	Headache, dizziness, nausea, heartbeat irregularities.
<b>Ingestion:</b>	No adverse effects due to ingestion are expected.
<b>Skin Contact:</b>	Frostbite.
<b>Eye contact:</b>	Frostbite.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

<b>Oral</b>	
<b>Product:</b>	Not classified for acute toxicity based on available data.
<b>Dermal</b>	
<b>Product:</b>	Not classified for acute toxicity based on available data.
<b>Inhalation</b>	
<b>Product:</b>	Not classified for acute toxicity based on available data.

#### Repeated dose toxicity

<b>Product:</b>	Mild toxic effect.
-----------------	--------------------

#### Skin Corrosion/Irritation

<b>Product:</b>	No data available.
-----------------	--------------------

#### Components:

1,3-Butadiene	Not likely, due to the form of the product. Frostbite hazard - rapidly expanding gas or liquid may cause frostbite.
n-Butane	Gas may be mildly irritating. Contact with the liquefied or pressurized gas may cause frostbite.
1-Butene	Gas may be mildly irritating. Contact with liquid form may cause frostbite.

#### Serious Eye Damage/Eye Irritation

<b>Product:</b>	No data available.
-----------------	--------------------



**Components:**

1,3-Butadiene	Irritant of eyes and mucous membranes. Frostbite hazard - rapidly expanding gas or liquid may cause frostbite.
n-Butane	Gas may be mildly irritating. Contact with the liquefied or pressurized gas may cause momentary freezing followed by swelling and eye damage.
1-Butene	Gas may be mildly irritating. Contact with liquefied gas might cause frostbites, in some cases with tissue damage.

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** May cause cancer.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

1,3-Butadiene Overall evaluation: 1. Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

1,3-Butadiene Known To Be Human Carcinogen.

**ACGIH Carcinogen List:**

1,3-Butadiene Group A2: Suspected human carcinogen.

**Germ Cell Mutagenicity****In vitro**

**Product:** May cause genetic defects.

**In vivo**

**Product:** May cause genetic defects.

**Reproductive toxicity**

**Product:** Not classified.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** Not classified

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Components:**

1,3-Butadiene	Liver, Blood, Lungs, ovaries, testes
2-Butene	Nervous system

**Aspiration Hazard**

**Product:** not applicable

**Other effects:** No data available.

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:****Fish**

**Product:** Harmful to aquatic life.

**Aquatic Invertebrates****Product:** Harmful to aquatic life.**Toxicity to aquatic plants****Product:** Harmful to aquatic life.**Chronic hazards to the aquatic environment:****Fish****Product:** Harmful to aquatic life with long lasting effects.**Aquatic Invertebrates****Product:** Harmful to aquatic life with long lasting effects.**Toxicity to aquatic plants****Product:** Harmful to aquatic life with long lasting effects.**Persistence and Degradability****Biodegradation****Product:** Product is likely to biodegrade.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** Bioconcentration Factor (BCF): 10 (estimated) (1,3-butadiene)**Partition Coefficient n-octanol / water (log Kow)****Product:** 1.99 (1,3-butadiene)**Mobility in Soil:**

Expected to have high mobility in soil. (1,3-butadiene)

**Other Adverse Effects:**

No data available.

**13. Disposal considerations****Disposal instructions:**

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Waste generator is advised to carefully consider hazardous properties and control measures needed for other materials that may be found in the waste.

**Contaminated Packaging:**

Check local, federal and provincial environmental regulations prior to disposal.

**14. Transport information****TDG**

UN Number:	UN 1010
UN Proper Shipping Name:	BUTADIENES, STABILIZED
Class	2.1
Packing Group	–
Label(s)	2.1
Subsidiary risk label	–
Special precautions for user:	Emergency Response Guidebook No. 116P, latest revision. For road, rail and marine shipments, ensure product is transported with the addition of a suitable inhibitor / stabilizer, such as t-butyl catechol (TBC) or equivalent.

## 15. Regulatory information

### Canada Federal Regulations

#### List of Toxic Substances (CEPA, Schedule 1)

##### Chemical Identity

1,3-Butadiene

#### Export Control List (CEPA 1999, Schedule 3)

Not regulated

#### National Pollutant Release Inventory (NPRI)

##### Canada. Canadian Environmental Protection Act (CEPA). National Pollutant Release Inventory (NPRI) (Parts 1-4)

NPRI 1,3-Butadiene

##### Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements

NPRI PT5 1,3-Butadiene  
n-Butane  
1-Butene  
2-Butene  
Propane, 2-methyl-  
Propane, 2,2-dimethyl-

#### Greenhouse Gases

Not regulated

#### Precursor Control Regulations

Not regulated

#### Canada. Substances Subject to Significant New Activity (SNAc) Reporting Requirements

Not regulated

#### Inventory status

Canada DSL Inventory List: On or in compliance with the inventory

## 16. Other information, including date of preparation or last revision

**Issue Date:** 01/29/2020

**Revision Information:** 01/29/2020: SDS Update

**Version #:** 7.0

**Abbreviations and acronyms:** ACGIH = American Conference of Governmental Industrial Hygienists; BOD = Biochemical Oxygen Demand; CAS = Chemical Abstracts Service; CEPA = Canadian Environmental Protection Act; COD = Chemical Oxygen Demand; DSL = Domestic Substances List; EC50 = Effective Concentration 50%; EPA = Environmental Protection Agency; GHS = Globally Harmonized System for the Classification and Labelling of Chemicals; IARC = International Agency for Research on Cancer; IDLH = Immediately Dangerous to Life or Health; Kow = Octanol/water partition coefficient; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; LEL = Lower Explosive Limit; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OEL = Occupational Exposure Limit; OSHA = Occupational Safety and Health Administration; PNOC = Particulates Not Otherwise Classified; PPE = Personal Protective Equipment; REL = Recommended Exposure Limit; SCBA = Self Contained Breathing Apparatus; SDS = Safety Data Sheet; STEL = Short Term Exposure Limit; TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average

**Further Information:** For additional information on equipment bonding and grounding, refer to the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or

National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity".

For additional information on properties, health and environmental hazard information, regulatory overview, handling, transport and storage, fire safety and emergency response, please refer to the, "Butadiene Product Stewardship Guidance Manual", updated November 27, 2019, by the American Chemistry Council ([www.americanchemistry.com](http://www.americanchemistry.com))

For additional information on the safe handling of butadiene, please refer to the "Butadiene Popcorn Polymer Resource Book" (in CD format), published by the International Institute of Synthetic Rubber Producers, Inc. (IISRP) ([www.iisrp.com](http://www.iisrp.com))

**Disclaimer:**

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, **NOVA CHEMICALS MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY NOVA CHEMICALS OR OTHERS IS TO BE INFERRED. THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT NOVA CHEMICALS FOR THE MOST CURRENT VERSION OF THIS SDS. NOVA CHEMICALS DOES NOT ASSUME RESPONSIBILITY FOR SDS OBTAINED FROM THIRD PARTY SOURCES.**

**UNLESS SPECIFICALLY AGREED OTHERWISE, NOVA CHEMICALS DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL OF THE PRODUCT/MATERIALS DESCRIBED HEREIN.**