

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended by Commission Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier	
	Product name:	

NOVAPOL® Polyethylene

Other means of identification

Synonyms, Trade	HDPE, HPLDPE, LDPE, LLDPE, LMDPE, MDPE Polyethylene resins, ethylene
Names:	polymers
SDS number:	NOVA-0029C

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Thermoplastic resin extruded into film, sheet or moulded into containers and other shapes. **Uses advised against:** All uses other than the identified.

1.3 Details of the supplier of the safety data sheet

Non EU Supplier

Company Name:	NOVA Chemicals International (SA)
Address:	Avenue de la Gare 14
	1700 Fribourg, Switzerland
Telephone:	+41-26-426-5757
SDS Information	msdsemail@novachem.com
Email:	

REACH Only Representative

Company Name:	Intertek Deutschland GmbH
Address:	Stangenstrasse 1
	Leinfelden-Echterdingen, Germany 70771
Telephone:	+49-711-27311-0
SDS Information	ies02.reach@intertek.com
Email:	

1.4 Emergency telephone number:

+1-800-561-6682, +1-403-314-8767 (NOVA Chemicals) (24 hours) **Europe:** +44 1235 239670 (NCEC) (24 Hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous according to the legislation in force.

Classification according to Regulation (EC) No 1272/2008 as amended.

Not classified

2.2 Label elements

Hazard Symbol: No symbol



Signal Word:	No signal word.
Hazard Statement(s):	not applicable
Precautionary Statemen	ts:
Prevention:	 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240: Ground and bond container and receiving equipment. P241: Use explosion-proof [electrical/ventilating/lighting] equipment. P264: Wash hands thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. P284: [In case of inadequate ventilation] wear respiratory protection.
Response:	 P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P313: Get medical advice/attention. P302+P352: IF ON SKIN: Wash with plenty of water/soap. P332+P313: If skin irritation occurs: Get medical advice/attention. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage:	P401: Store in accordance with local/regional/national regulations. P410: Protect from sunlight.
Disposal:	P501: Dispose of contents/container in accordance with local/regional/national/international regulations. P502: Refer to manufacturer or supplier for information on recovery or recycling.
2.3 Other hazards	If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. Spilled product may create a dangerous slipping hazard. PBT assessment does not apply.
	 Endocrine Disruption-Toxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Endocrine Disruption-Ecotoxicity The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information:	No hazardous ingredients.
SDS_GR	



SECTION 4: First aid measures

4.1 Description of first aid measures Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. Skin Contact: IF ON SKIN: Wash with plenty of water/soap. If skin irritation occurs: Get medical advice/attention. Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention. 4.2 Most important symptoms and effects, both acute and delayed: Thermal burns. Respiratory irritation. Mechanical irritation. 4.3 Indication of any immediate medical attention and special treatment needed Treatment: After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Moten resi will come off as healing occurs; therefore, immediate medical removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected. SECTION 5: Firefighting measures Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Suitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire. Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as wel		
Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention. 4.2 Most important symptoms and effects, both acute and delayed: Thermal burns. Respiratory irritation. Mechanical irritation. 4.3 Indication of any immediate medical attention and special treatment needed After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as themal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected. SECTION 5: Firefighting measures General Fire Hazards: Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. Unsuitable extinguishing media: Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydroachoras well as carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein), Inhalation of these decomposition products may be facustared. Several material may form explosive mixtures: Risk of dust-crist explosion is increased if flammable vapours are also present. Static discharge: material carbon disc		IF INHALED: Remove person to fresh air and keep comfortable for
contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention. 4.2 Most important symptoms and effects, both acute and delayed: Thermal burns. Respiratory irritation. Mechanical irritation. 4.3 Indication of any immediate medical attention and special treatment needed After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs: therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected. SECTION 5: Firefighting measures General Fire Hazards: Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Suitable extinguishing media: Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. 4.2 Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: 5.3 Advice for firefighting procedures or divide	Skin Contact:	
advice/attention. 4.2 Most important symptoms and effects, both acute and delayed: 4.3 Indication of any immediate medical attention and special treatment needed Treatment: After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected. SECTION 5: Firefighting measures Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Suitable extinguishing media: Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or form. 4.2 Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decorposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Stati clicknarge. 5.3 Advice for firefighters Special fire-fighting procedures: Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire form maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefuly do void creating airborn dust. Fine dust dispersed in	Eye contact:	contact lenses, if present and easy to do. Continue rinsing. Get medical
and effects, both acute and delayed:4.3 Indication of any immediate medical attention and special treatment needed Treatment:After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected.SECTION 5: Firefighting measuresGeneral Fire Hazards:Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke.5.1 Extinguishing media Suitable extinguishing media:Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam.Unsuitable extinguishing media:Avoid water in straight hose stream; will scatter and spread fire.5.2 Special hazards arising from the substance or mixture:Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: special fire-fighting procedures:5.3 Advice for firefighters Special fire-fighting procedures:Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or	Ingestion:	•
Treatment:After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are expected.SECTION 5: Firefighting measuresPolyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke.5.1 Extinguishing media Suitable extinguishing media:Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam.4.2 Upsuitable extinguishing media:Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge.5.3 Advice for firefighters Special fire-fighting procedures:Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborm dust. Fine dust dispersed in air in	and effects, both acute and	Thermal burns. Respiratory irritation. Mechanical irritation.
General Fire Hazards: Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Suitable extinguishing media: Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. Unsuitable extinguishing media: Vater fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. 5.2 Special hazards arising from the substance or mixture: Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge. 5.3 Advice for firefighters Special fire-fighting procedures: Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in		After adequate first aid, no further treatment is required unless symptoms reappear. Burns should be treated as thermal burns. Molten resin will come off as healing occurs; therefore, immediate removal from the skin is not necessary. Treatment should be directed at the control of symptoms and the clinical condition of the patient. No adverse effects due to ingestion are
General Fire Hazards: Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating smoke. 5.1 Extinguishing media Suitable extinguishing media: Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. Unsuitable extinguishing media: Vater fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam. 5.2 Special hazards arising from the substance or mixture: Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge. 5.3 Advice for firefighters Special fire-fighting procedures: Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in	SECTION 5: Firefighting meas	Sures
Suitable extinguishing media:Water fog or water spray. Small fires: Dry chemical, carbon dioxide (CO2) or foam.Unsuitable extinguishing media:Avoid water in straight hose stream; will scatter and spread fire.5.2 Special hazards arising from the substance or mixture:Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge.5.3 Advice for firefighters Special fire-fighting procedures:Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in	General Fire Hazards:	Polyethylene is a noncombustible solid, but dusts may form explosive mixtures in air. Product will burn at high temperatures but is not considered flammable. Under fire conditions, product will readily burn and emit irritating
 media: 5.2 Special hazards arising from the substance or mixture: Upon heating, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge. 5.3 Advice for firefighters Special fire-fighting procedures: 	Suitable extinguishing	
 from the substance or mixture: oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical discharge. 5.3 Advice for firefighters Special fire-fighting procedures: Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in 		Avoid water in straight hose stream; will scatter and spread fire.
Special fire-fighting procedures:Keep upwind. Keep unauthorised personnel away. Move containers from fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in	from the substance or	oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present. Static discharge: material can accumulate static charges which may cause an incendiary electrical
	Special fire-fighting	fire area if you can do so without risk. Fight fire from maximum distance or use unmanned holders or monitor nozzles. Apply extinguishing media carefully to avoid creating airborne dust. Fine dust dispersed in air in



potential dust explosion hazard. Water may be used to flood the area. Use water spray to cool fire exposed surfaces and to protect personnel. Avoid inhaling any smoke and combustion materials. Remove and isolate contaminated clothing and shoes. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.


Special protective	Wear positive pressure self-contained breathing apparatus (SCBA).
equipment for fire-fighters:	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Isolate area. Alert stand-by emergency and fire-fighting personnel. Wear appropriate personal protective equipment. For additional information, refer to Section 8.
6.2 Environmental precautions:	Prevent entry into waterways, sewer, basements or confined areas.
6.3 Methods and material for containment and cleaning up:	Avoid standing or walking on spilled product. Spilled product may create a dangerous slipping hazard. In case of leakage, eliminate all ignition sources. Stop leak if safe to do so. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Use appropriate tools to put the spilled solid in an appropriate disposal or recovery container. Use non-sparking tools. Recover and reclaim or recycle, if practical.
6.4 Reference to other sections:	See Section 8 for recommended Personal Protective Equipment and see Section 13 for waste disposal considerations.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Keep away from uncontrolled heat and incompatible materials. Wash hands thoroughly after handling. Minimise dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Ground all material handling and transfer equipment. For additional information on control of static and minimizing potential dust and fire hazards, refer to NFPA-654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing and Handling of Combustible Particulate Solids", current edition. Use in a well-ventilated area. Wear eye protection/protective gloves as needed/wear full face-shield during thermal processing if contact with molten material is possible/wear respirator if dusty. Spilled product may create a dangerous slipping hazard. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities:	Store in accordance with all current regulations and standards. Storage area should be clearly identified, well-illuminated and clear of obstruction. Store in closed, grounded and properly designed vessels. Keep away from uncontrolled heat and incompatible materials. Protect from sunlight. Outdoor storage of product in bags requires protection from ultra-violet sunlight by use of a UV stabilized bag or alternate means. Avoid



8.1	Control parameters Dccupational Exposure Limits		
		During dusty conditions ACGIH recommends for Particles (insoluble or poorly soluble) not otherwise specified a TWA of 10 mg/m3 (inhalable particles), 3 mg/m3 TWA (respirable particles).	
8.2	Exposure controls		
	Appropriate Engineering Controls:	Engineering methods to reduce hazardous exposure are preferred controls. Methods include mechanical ventilation (dilution and local exhaust) process or personal enclosure, remote and automated operation, control of process conditions, leak detection and repair systems, and other process modifications. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Ensure all exhaust ventilation systems are discharged to outdoors, away from air intakes and ignition sources. Supply sufficient replacement air to make up for air removed by exhaust systems. Administrative (procedure) controls and use of personal protective equipment may also be required. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Use only appropriately classified electrical equipment and powered industrial trucks.	
	Individual protection measure	es, such as personal protective equipment	
	General information:	Personal protective equipment (PPE) should not be considered a long-term solution to exposure control. Employer programs to properly select, fit, maintain and train employees to use equipment must accompany PPE. Consult a competent industrial hygiene resource, the PPE manufacturer's recommendation, and/or applicable regulations to determine hazard potential and ensure adequate protection.	
	Eye/face protection:	Safety glasses. Wear a face shield when working with molten material.	
	Skin protection Hand Protection:	Wear gloves to protect against thermal burns.	
	Other:	Wear appropriate clothing to prevent any possibility of skin contact. Wear work clothes with long sleeves and pants. Safety footwear with good traction is recommended to help prevent slipping. Static Dissipative (SD) rated footwear is also recommended.	
	Respiratory Protection:	Appropriate approved air-purifying respirator that meets the requirements of the European Standard for Respiratory Protection (EN 149) or self-	

NOVA Chemicals®	Version: 1.0 Date of previous report version: - Generation date: 10.05.2024
	Date of first report version: 10.05.2024
	contained breathing apparatus should be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
Hygiene measures:	Use effective control measures and PPE to maintain worker exposure to concentrations that are below these limits. Ensure that eyewash stations and safety showers are in close proximity to work locations.
Environmental Controls:	Follow all applicable environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance **Physical state:** solid Form: Pellets or Granular powder Colour: white / colourless / translucent Odour: Minimal, Mild **Odour Threshold:** No data available. Melting point/freezing point: 105 - 135 °C (221 - 275 °F) (Melting Point) 85 - 127 °C (185 - 261 °F) (Softening point) Initial boiling point and boiling range: not applicable Flammability: May form combustible dust concentrations in air [if small particles are generated during further processing, handling or by other means.] Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): not applicable Flammability limit - lower(%): not applicable Flash Point: not applicable Auto-ignition temperature: No data available. **Decomposition temperature:** > 300 °C (> 572 °F) pH: not applicable Viscosity Kinematic viscosity: not applicable Solubility(ies) Solubility in water: Insoluble in water. Solubility (other): No data available. Partition coefficient (n-octanol/water): not applicable Vapour pressure: not applicable **Relative density:** 0,905 - 0,965 **Density:** 905 - 965 kg/m3 **Relative vapour density:** not applicable Vapour density: not applicable Particle characteristics Particle Size: 0,1 - 5 MM 9.2 Other information **Explosive properties:** No data available. **Oxidising Properties:** not applicable **Evaporation Rate:** not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
10.2 Chemical stability:	Material is stable under normal conditions.
10.3 Possibility of hazardous reactions:	Hazardous polymerization not likely to occur.
10.4 Conditions to avoid:	Avoid exposing to extended periods of heat and contact with strong oxidizing substances.
10.5 Incompatible Materials:	Strong oxidising agents. Organic solvents, ether, gasoline, lubricating oils, chlorinated hydrocarbons and aromatic hydrocarbons may react with and degrade polyethylene. Powdered material may form explosive dust-air mixtures. Risk of dust-air explosion is increased if flammable vapours are also present.
10.6 Hazardous decomposition products:	Upon decomposition, polyethylene may emit various oligomers, waxes and oxygenated hydrocarbons as well as carbon dioxide, carbon monoxide and small amounts of other organic vapours (e.g. aldehydes, acrolein). Inhalation of these decomposition products may be hazardous.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation:	During processing, thermal fumes and inhalation of fine particles may cause respiratory irritation.
Skin Contact:	During processing, contact with powder or fines may cause mechanical irritation. Molten material will produce thermal burns.
Eye contact:	During processing, contact with powder or fines may cause mechanical irritation. Molten material will produce thermal burns.
Ingestion:	Ingestion of this product is not a likely route of exposure.
Symptoms related to the physical, chemical and toxicological characteristics	
Symptoms related to the physic	al, chemical and toxicological characteristics
Symptoms related to the physic Inhalation:	al, chemical and toxicological characteristics Respiratory irritation.
Inhalation:	Respiratory irritation. Mechanical irritation. Thermal burns. Negligible irritation of the skin based

11.1 Information on toxicological effects

Acute toxicity	
Oral Product:	LD 50: > 5.000 mg/kg (estimated)
Dermal Product:	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritat Product:	ion No data available.
Respiratory or Skin Sensitisation Product:	on No data available.
Germ Cell Mutagenicity	
In vitro Product:	There are no known or reported genetic effects.
In vivo Product:	There are no known or reported genetic effects.
Carcinogenicity Product:	Not classified
Reproductive toxicity Product:	There are no known or reported reproductive effects.
Specific Target Organ Toxicity Product:	- Single Exposure No data available.
Specific Target Organ Toxicity Product:	- Repeated Exposure No data available.
Aspiration Hazard Product:	Not classified.
11.2 Information on other hazards	
Endocrine disrupting properties Product:	s The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission



Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information Product:	No data available.
SECTION 12: Ecological inform	nation
General information:	NOVAPOL® resins are expected to be inert in the environment. They float on water and are not biodegradable. They are not expected to bioconcentrate (accumulate in the food chain) due to their high molecular weight. NOVAPOL® resins are not expected to be toxic if ingested but may represent a choking hazard if ingested by waterfowl or aquatic life.
12.1 Toxicity	
Acute toxicity	
Fish Product:	LC 50 (96 h): > 100 mg/l
Aquatic Invertebrates Product:	EC 50 (Daphnia magna, 48 h): > 100 mg/l
Toxicity to aquatic plants Product:	EC 50 (72 h): > 100 mg/l
Chronic toxicity	
Fish Product:	NOEC : > 100 mg/l
Aquatic Invertebrates Product:	NOEC : > 100 mg/l
Toxicity to aquatic plants Product:	NOEC : > 100 mg/l
12.2 Persistence and degradabili	ity
Biodegradation Product:	Not readily degradable. Under optimal oxidation conditions, >99% of polyethylene will remain intact after exposure to microbial actions. Product will slowly change (embrittle) in the presence of sunlight, but will not fully breakdown. Product buried in landfill has been found to be stable over time. No toxic degradation products are known to be produced.
BOD/COD Ratio Product	No data available.
12.3 Bioaccumulative potential Bioconcentration Factor (BC Product:	CF) Polyethylene resins may accumulate in the digestive systems of birds and aquatic life, causing injury and possible death due to starvation.
Partition Coefficient n-octan Product:	nol / water (log Kow) not applicable
12.4 Mobility in soil: SDS_GR	Biologically persistent. This product has not been found to migrate through 9/13



soils.

12.5 Results of PBT and vPvB as	
Product	PBT assessment does not apply.
12.6 Endocrine disrupting prope	rties:
Product:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects:	Polyethylene resins are persistent in aquatic and terrestrial systems.
SECTION 13: Disposal conside	erations
13.1 Waste treatment methods	
Disposal methods:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Preferred disposal methods for polyethylene in order of preference are: 1) clean and reuse if possible, 2)

characteristics at time of disposal. Preferred disposal methods for polyethylene in order of preference are: 1) clean and reuse if possible, 2) recover and resell through plastic recyclers or resin brokers, 3) incinerate with waste heat recovery and 4) landfill. DO NOT ATTEMPT TO DISPOSE OF BY UNCONTROLLED INCINERATION. Open burning of plastics at landfills should not be undertaken.

Contaminated Packaging: Check regional, national and local environmental regulations prior to disposal.

SECTION 14: Transport information

ADR

Not Regulated.

IMDG

Not Regulated.

ΙΑΤΑ

Not Regulated.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation 1005/2009/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: None present or none present in regulated quantities.

EU. Reach Annex XIV, Substances Subject to Authorization: None present or none present in regulated quantities.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended: None present or none present in regulated quantities.

EU. Directive 2010/75/EU on Industrial Emissions (IPPC), Annex II, L 334/17: None present or none



present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: None present or none present in regulated quantities.

EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC): None present or none present in regulated quantities.

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use: None present or none present in regulated quantities.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.: None present or none present in regulated quantities.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.: None present or none present in regulated quantities.

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.: None present or none present in regulated quantities.

EU. Regulation No. 166/2006 PRTR (Pollutant Release and Transfer Registry), Annex II: Pollutants: None present or none present in regulated quantities.

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work: None present or none present in regulated quantities.

EU. Restricted (Annex I) & Reportable (Annex II) Explosives Precursors, Regulation 2019/1148/EU on Explosives Precursors (EU EXPLD): None present or none present in regulated quantities.

EU. Annexes I and II, Regulation 98/2013/EU on the Marketing and Use of Explosives Precursors (EU EXPRE): None present or none present in regulated quantities.

EU. Restricted Explosives Precursors: Annex I, Regulation 2019/1148/EU on Explosives Precursors (EUEXPL1D): None present or none present in regulated quantities.

EU. Reportable (Annex II) Explosives Precursors, Regulation 2019/1148/EU on Explosives Precursors (EUEXPL2D): None present or none present in regulated quantities.

EU. Reportable (Annex II) Explosives Precursors, Regulation 2019/1148/EU on Explosives Precursors (EUEXPL2L): None present or none present in regulated quantities.

15.2 Chemical safety assessment:	Not required. This product complies with the registration requirements of
	the REACH Regulation (EC) No 1907/2006. The component substances
	have been duly registered or are exempt from registration. This covers
	those EU importers included in NOVA Chemicals' Only Representative
	scheme.

SECTION 16: Other information



References PBT vPvB	PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.
Key literature references and sources for data:	Available on request.
Wording of the H-statements i	n sections 2 and 3: none
Training information:	Suitable information on safety in handling, storage and processing the product should be given to employees based on the existing information.
Other information:	Exposure to the Hazardous Combustion and Decomposition Products as described in the SDS, Sections 5 and 10, may be linked with various acute and chronic health effects. These effects include irritation of eyes and upper respiratory tract primarily from the aldehydes, breathing difficulties, systemic toxicity such as liver, kidney, and central nervous system effects.
	NOVA Chemicals has monitored worker exposures to emissions during commercial-scale processing of polyethylene. Concentrations of hazardous decomposition products were determined to be well below established exposure limits in the workplace. "Quantitation of Employee Exposure to Emission Products Generated By Commercial-Scale Processing of Polyethylene" is available in the Am. Ind. Hyg. Assoc. J. 56:809-814 (1995) and "Quantification of Emission Compounds Generated During Commercial- Scale Processing of Advanced SCLAIRTECH™ Polyethylene" is available in the Journal of Plastic Film & Sheeting Volume 26 Issue 2, April 2010.
	For information on ventilation considerations for the control of volatile air contaminants from polyethylene, please request a copy of NOVA Chemicals' publication, "Ventilation Guidelines for Heat-Processing Polyethylene Resins".
	For additional information on unloading hopper cars containing plastic resins, refer to NOVA Chemicals' publication, "Hopper Car Unloading Guide".
	For information on processing properties, selection of NOVAPOL resin grades, refer to the NOVAPOL Product Data Sheets available on our web site, under Products & Applications: <u>http://www.novachemicals.com</u> .
	For additional information on preventing polyethylene resin loss, refer to published plastic industry publications and resources under Operation Clean Sweep® product stewardship program; now downloadable from the web at <u>http://www.opcleansweep.org/</u> .
	Polyethylene fines and dust particles are listed as a Class I combustible dust by the National Fire Protection Association (see NFPA-68, Table F.1 (e)). For additional information on control of static and minimizing potential dust and fire hazards, refer to NFPA-654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing and Handling of Combustible Particulate Solids", current edition.
	Explosivity testing was done on one NOVAPOL® LLDPE, one LDPE and one HDPE resins with Pmax = $4.8-5.7$ bar, Kst = $12-17$ (bar m/s) and Minimum Ignition Energy (MIE) = $1000-10,000$; dust explosion class = St 1; this data was obtained for polyethylene with a final particle size of $100\% < 250$ um and moisture content between 0 and 0.2%. Similar results are expected for the remaining NOVAPOL® polyethylene resin grades.
SDS CP	For NOVAPOL resin grade specific information including food contact

NOVA Chemicals®	Version: 1.0 Date of previous report version: - Generation date: 10.05.2024 Date of first report version: 10.05.2024
	compliance statements, please contact your sales representative or refer to NOVA Chemicals' polyethylene Product Data Sheets.
Key/Legend:	ACGIH = American Conference of Governmental Industrial Hygienists; ADR = Transport of Dangerous Goods by Road; ADR/RID = European Agreement of Dangerous Goods by Road/Rail; CAS = Chemical Abstracts Service; DFG = Deutsche Forschungsgemeinschaft; EC50 = Effective Concentration 50%; EEC = European Economic Community; EU = European Union; GHS = Globally Harmonized System for the Classification and Labelling of Chemicals; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; ICAO = International Civil Aviation Organization; IMDG = International Maritime Dangerous Goods; IMO = International Maritime Organization; Kow = Octanol/water partition coefficient; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; LEL = Lower Explosive Limit; LFL = Lower Flammable Limit; LLV = Level Limit Ceiling Limit (Sweden dust); MAK = Maximum Concentration Value in the Workplace; NCEC = National Chemical Emergency Centre; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OEL = Occupational Exposure Limit; PNOC = Particulates Not Otherwise Classified; PPE = Personal Protective Equipment; REACH = Registration, Evaluation, Authorisation and Restriction of Chemical Substances; RID = Transport of Dangerous Goods by Rail; SADT = Self Accelerating Decomposition Temperature; SCBA = Self Contained Breathing Apparatus; SDS = Safety Data Sheet; STEL = Short Term Exposure Limit; TLV = Threshold Limit Value; TWA = Time Weighted Average; UEL = Upper Explosive Limit; UFL = Upper Flammable Limit; VLA-ED = Valor límite Ambiental de Exposición Diaria (Environmental Exposure Daily Limit Value); VME = valeur limite d'exposition (Occupational Exposure Limits)
Issue Date:	10.05.2024
SDS No.:	NOVA-0029C
Disclaimer:	ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, NOVA CHEMICALS MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCT/MATERIALS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). NO FREEDOM FROM INFRINGEMENT OF ANY PATENT OWNED BY NOVA CHEMICALS OR OTHERS IS TO BE INFERRED. THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. PLEASE CONTACT NOVA CHEMICALS FOR THE MOST CURRENT VERSION OF THIS SDS. NOVA CHEMICALS DOES NOT ASSUME RESPONSIBILITY FOR SDS OBTAINED FROM THIRD PARTY SOURCES. UNLESS SPECIFICALLY AGREED OTHERWISE, NOVA CHEMICALS DOES NOT TAKE RESPONSIBILITY FOR USE, TRANSPORTATION, STORAGE, HANDLING OR DISPOSAL OF THE PRODUCT/MATERIALS DESCRIBED HEREIN.
•	

NOVA Chemicals®

is a registered trademark of NOVA Brands Ltd.; authorized use/utilisation autorisée.

Advanced SCLAIRTECH[™] is a trademark of NOVA Chemicals.

Operation Clean Sweep® is a registered service mark of Plastics Industry Association, Inc.

NOVAPOL® is a registered trademark of NOVA Brands Ltd.; authorized use/utilisation autorisée.