



# SCLAIR® IG464-U Resin

## Homopolymer HDPE Injection Molding Resin

Property		ASTM (1)	Туріс	al Values <sup>(2)</sup>
Melt Index <sup>(3)</sup>		D 1238	10.0	0 g/10 min
Density		D 792	0.964	4 g/cm³
			METRIC UNITS	ENGLISH UNITS
Tensile Strength - Yield	(4)	D 638	33 MPa	4,800 psi
Tensile Strength - Break	(4)	D 638	20 MPa	2,900 psi
Elongation - Break	(4)	D 638	1,250 %	
Flexural Modulus - 1% Secant	(5)	D 790	1,700 MPa	246,600 psi
Durometer Hardness - Shore D		D 2240	68	
Vicat Softening Temperature	(6)	D 1525	131 °C	268 °F

(1) Properties designated have been determined using methods which are in accordance with, or substantially in accordance with,	,
the specified testing standards.	

- (2) Typical Values represent average laboratory values and are intended as guides only, not as specifications.
- (3) Condition 190°C/2.16 kg.
- (4) 50 mm/min (2 in/min), Type IV specimen.
- (5) Procedure B.
- (6) 10 N, 120°C/h.

Melt Index	10.0
Density	0.964

#### **Features**

- Superior stiffness allows for part thinwalling and improved stack strength
- Low viscosity for exceptional processability, shorter cycle times and energy savings
- Exceptional physical properties provide impact resistance for demanding applications
- Low warpage for improved part quality and reliability

#### **Additives**

- Processing antioxidant
- UV stabilizer

## **Applications**

- Crates
- Pallets
- Totes
- Pails





# SCLAIR IG464-U Resin

# Homopolymer HDPE Injection Molding Resin

### **Availability**

SCLAIR IG464-U polyethylene resins are available in bulk hopper cars, hopper trucks, boxes, sea bulk containers, or bags. The product type and batch number are clearly marked on each container. Contact the NOVA Chemicals sales office nearest you for availability in your area.

### Storage/Handling

SCLAIR IG464-U resin should be stored in a clean, dry place at ambient temperatures. Prolonged or improper storage can result in deterioration of product properties. Care should be taken when handling and transferring product to prevent foreign matter contamination. The NOVA Chemicals Safety Data Sheet (SDS) contains important safety information and should be reviewed before using the product.

### **Processing Conditions**

Comprehensive assistance with processing conditions and technology is available from NOVA Chemicals Technical Service at (403) 291-8444.

### **Food Packaging Status**

United States: SCLAIR IG464-U resin complies with the specifications contained in the FDA regulation 21 CFR 177.1520 for olefin polymers, para. (c) 2.2, and may thus be used in the United States as an article or component of an article intended for use in contact with food. This resin is subject to the specific limitation that it may contact food only at temperatures of 212°F and below (21 CFR 176.170(c) Table 2, conditions of use B–H).

Other Countries: For regulatory compliance information for other countries, please contact your nearest NOVA Chemicals office.

#### **Environmental**

NOVA Chemicals polyethylene resins are biologically and chemically inert, but improper disposal may present an ingestion hazard to wildlife. Where recycling of NOVA Chemicals' polyethylene resins is not possible, disposal to landfill or incineration in accordance with all applicable government laws and regulations is recommended. Please contact NOVA Chemicals Technical Service for further information on recycling and disposal of NOVA Chemicals resins.



is the SPI resin code developed for high density polyethylene to identify material type for sorting and recycling purposes.

The NOVA Chemicals logo is a registered trademark of NOVA Brands Ltd.; authorized use/utilisation autorisée. SCLAIR® is a registered trademark of NOVA Chemicals Corporation in Canada and of NOVA Chemicals (International) S.A. elsewhere; authorized use/utilisation autorisée.

The above information is provided in good faith. NOVA Chemicals is not responsible for any processing or compounding which may occur to produce finished articles, packaging materials or their components. Further, NOVA CHEMICALS MAKES NO WARRANTY OR REPRESENTATION OF ANY KIND, REGARDING THE INFORMATION GIVEN FOR THE PRODUCTS DESCRIBED, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES, REPRESENTATIONS AND CONDITIONS, INCLUDING WITHOUT LIMITATION ALL WARRANTIES AND CONDITIONS OF QUALITY, MERCHANTABILITY AND SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Responsibility for use, storage, handling and disposal of the products described herein is that of the purchaser or end user.

June 16, 2023

